U.S.S.N.: 10/706,850 Filed: 12-Nov-2003

Page 2

This listing of claims replaces all prior versions and listings of claims in the application.

Listing of Claims:

1. (Currently Amended) A computerized method of video analysis comprising:

receiving, at a computerized receiving device, a plurality of series of video frames generated by a plurality of image sensors, each having a field-of-view, which that monitors a portion[[s]] of a monitored environment; and

concurrently tracking, using a tracking module, a plurality of objects with respect to the monitored environment as the objects move between fields-of-view based at least in part on a probability that one of the plurality of objects included in a first video frame generated by a first image sensor at a first point in time will be included in a second video frame generated by a second image sensor at a second point in time; and

concurrently tracking, <u>using the tracking module and</u> based on at least some of the received series of video frames, a plurality of objects with respect to the monitored environment and based on an analysis of the monitored environment over time and independent of calibration among the image sensors and the monitored environment.[[,]]

(i) the plurality of objects within the monitored environment as the objects move between fields of view, and ii) a plurality of objects within one field of view based on at least some of the received series of video frames.

- 2. (Original) The method of claim 1 wherein the image sensors are cameras.
- 3. (Cancelled)
- 4. (Original) The method of claim 1 further comprising:

storing a plurality of blob states over time, each state including a number of objects included in the blob and a blob signature; and

U.S.S.N.: 10/706,850 Filed: 12-Nov-2003

Page 3

storing a plurality of transition likelihood values representing the probability that objects

within one blob at one instant in time correspond to objects within other blobs at other instants in

time.

5. (Original) The method of claim 4 further comprising altering the stored transition

probabilities upon analysis of additional video frames.

6. (Original) The method of claim 4 further comprising storing object data indicating

correspondences between objects and blob states.

7. (Original) The method of claim 4 generating a tracking solution based on the blob states and

transition probabilities.

8. (Original) The method of claim 1 generating tracking metadata including at least one of

object track data, tracking solutions, object feature data and field-of-view data.

9. (Original) The method of claim 8 further comprising:

selecting a rule set to analyze generated tracking metadata; and

evaluating, using a rules engine, the tracking metadata based on the rule set.

10. (Original) The method of claim 9 further comprising selecting the rule set to monitor

parking lot security.

11. (Original) The method of claim 9 further comprising selecting the rule set to detect property

theft.

U.S.S.N.: 10/706,850 Filed: 12-Nov-2003

Page 4

12. (Original) The method of claim 9 further comprising selecting the rule set to detect hazards

to children.

13. (Original) The method of claim 9 further comprising selecting the rule set to monitor public

safety.

14. (Original) The method of claim 9 further comprising selecting the rule set to determine

merchandizing and operations statistics.

15. (Currently Amended) A computerized system for video analysis comprising:

a receiving module configured to receive a plurality of series of video frames, the series

of video frames generated over time by a plurality of image sensors which monitor portions of a

monitored environment and have a field-of-view; and

a calibration-independent tracking module in communication with the receiving module

and configured to i) concurrently track a plurality of objects with respect to within the monitored

environment as the objects move between fields-of-view based at least in part on a probability

that one of the plurality of objects included in a first video frame generated by a first image

sensor at a first point in time will be included in a second video frame generated by a second

<u>image sensor at a second point in time</u>, and ii) concurrently track a plurality of objects within one

field-of-view based on at least some of the received series of video frames and independent of

calibration among the image sensors and the monitored environment, the tracking module

outputting tracking metadata.

16. (Original) The system of claim 15 further comprising a rules engine in communication with

the tracking module and receiving the tracking metadata.

17. (Currently Amended) A system for monitoring parking lot security comprising:

a receiving module configured to receive a plurality of series of video frames, the series

U.S.S.N.: 10/706,850 Filed: 12-Nov-2003

Page 5

of video frames generated over time by a plurality of image sensors which monitor portions of a monitored environment and have a field-of-view;

a calibration-independent tracking module in communication with the receiving module and configured to i) concurrently track a plurality of objects with respect to within the monitored environment as the objects move between fields-of-view based at least in part on a probability that one of the plurality of objects included in a first video frame generated by a first image sensor at a first point in time will be included in a second video frame generated by a second image sensor at a second point in time, and ii) concurrently track a plurality of objects within one field-of-view based on at least some of the received series of video frames and independent of calibration among the image sensors and the monitored environment, the tracking module outputting tracking metadata; and

a rules engine utilizing a parking lot security rule set configured to receive and evaluate the tracking metadata.

18. (Currently Amended) A system for property theft detection comprising:

a receiving module configured to receive a plurality of series of video frames, the series of video frames generated over time by a plurality of image sensors which monitor portions of a monitored environment and have a field-of-view;

a calibration-independent tracking module in communication with the receiving module and configured to i) concurrently track a plurality of objects with respect to within the monitored environment as the objects move between fields-of-view based at least in part on a probability that one of the plurality of objects included in a first video frame generated by a first image sensor at a first point in time will be included in a second video frame generated by a second image sensor at a second point in time, and ii) concurrently track a plurality of objects within one field-of-view based on at least some of the received series of video frames and independent of calibration among the image sensors and the monitored environment, the tracking module outputting tracking metadata; and

a rules engine utilizing a theft detection rule set configured to receive and evaluate the tracking metadata.

U.S.S.N.: 10/706,850 Filed: 12-Nov-2003

Page 6

19. (Currently Amended) A system for child hazard detection comprising:

a receiving module configured to receive a plurality of series of video frames, the series of video frames generated over time by a plurality of image sensors which monitor portions of a monitored environment and have a field-of-view;

a calibration-independent tracking module in communication with the receiving module and configured to i) concurrently track a plurality of objects with respect to the monitored environment as the objects move between fields-of-view based at least in part on a probability that one of the plurality of objects included in a first video frame generated by a first image sensor at a first point in time will be included in a second video frame generated by a second image sensor at a second point in time, and ii) concurrently track a plurality of objects within one field-of-view based on at least some of the received series of video frames and independent of calibration among the image sensors and the monitored environment, the tracking module outputting tracking metadata; and

a rules engine utilizing a child safety rule set configured to receive and evaluate the tracking metadata.

20. (Currently Amended) A system for property theft detection comprising:

a receiving module configured to receive a plurality of series of video frames, the series of video frames generated over time by a plurality of image sensors which monitor portions of a monitored environment and have a field-of-view;

a calibration-independent tracking module in communication with the receiving module and configured to i) concurrently track a plurality of objects with respect to within the monitored environment as the objects move between fields-of-view based at least in part on a probability that one of the plurality of objects included in a first video frame generated by a first image sensor at a first point in time will be included in a second video frame generated by a second image sensor at a second point in time, and ii) concurrently track a plurality of objects within one field-of-view based on at least some of the received series of video frames and independent of calibration among the image sensors and the monitored environment, the tracking module outputting tracking metadata; and

U.S.S.N.: 10/706,850 Filed: 12-Nov-2003

Page 7

a rules engine utilizing a public safety monitoring rule set configured to receive and

evaluate the tracking metadata.

21. (Currently Amended) A system for merchandizing and operations statistical analysis

comprising:

a receiving module configured to receive a plurality of series of video frames, the series

of video frames generated over time by a plurality of image sensors which monitor portions of a

monitored environment and have a field-of-view;

a calibration-independent tracking module in communication with the receiving module

and configured to i) concurrently track a plurality of objects with respect to within the monitored

environment as the objects move between fields-of-view based at least in part on a probability

that one of the plurality of objects included in a first video frame generated by a first image

sensor at a first point in time will be included in a second video frame generated by a second

image sensor at a second point in time, and ii) concurrently track a plurality of objects within one

field-of-view based on at least some of the received series of video frames and independent of

calibration among the image sensors and the monitored environment, the tracking module

outputting tracking metadata; and

a rules engine utilizing a merchandizing and operations statistical rule set configured to

receive and evaluate the tracking metadata.

22. (Withdrawn) A method of analyzing video data comprising: receiving tracking metadata

from a calibration-independent tracking module; analyzing the metadata; generating an event if a

portion of the metadata exhibits a specified pattern; and analyzing the metadata using a regular

expression representation of the specified pattern.

23. (Withdrawn) The method of claim 22, further comprising: comparing the regular

expression of the specified pattern to the portion of the metadata by utilizing a software

implemented representation of a finite state machine.

LIBC/3720605.1

U.S.S.N.: 10/706,850 Filed: 12-Nov-2003

Page 8

24. (Withdrawn) A system of video analysis comprising:

means for receiving tracking metadata from a calibration-independent tracking module; means for analyzing the metadata;

means for generating an event if a portion of the metadata exhibits specified pattern; and means for analyzing the metadata using a regular expression representation of the specified pattern.

- 25. (Previously Presented) The method of claim 1 wherein the fields-of-view are non-overlapping.
- 26. (Previously Presented) The system of claim 15 wherein the fields-of-view are non-overlapping.
- 27. (Previously Presented) The system of claim 17 wherein the fields-of-view are non-overlapping.
- 28. (Previously Presented) The system of claim 18 wherein the fields-of-view are non-overlapping.
- 29. (Previously Presented) The system of claim 19 wherein the fields-of-view are non-overlapping.
- 30. (Previously Presented) The system of claim 20 wherein the fields-of-view are non-overlapping.
- 31. (Previously Presented) The system of claim 21 wherein the fields-of-view are non-overlapping.